

RELAX GLOBE

TECHNOLOGY



Uscita Fumi Posteriore

Rear Exhaust Fume Outlet - Salida De Humos Trasera - Sortie De Fumée Arrière - Rauchausgang Hinten



OPTIONAL



Potenza Globale
Global Power
Puissance globale
Potencia global
Verbrennungsleistung

Rendimento totale
Total efficiency
Puissance globale
Potencia global
Pellet Wirkungsgrad

Peso
Weight
Poids
Gewicht

Consumo min-MAX
Min-Max consumption
Consumation min-MAX
Consumo min-maxi
Min-Maxi verbrauch

Temperatura gas di scarico
Exhaust gas temperature
Température des gaz d'échappement
Temperatura de los gases de escape
Abgas Temperatur

Tiraggio richiesto in funzionamento
Draw required in operation
Dessiner nécessaire en fonctionnement
Dibujar requerido en la operación
Erforderlicher Betriebszug

Uscita fumi
Chimney Output
Sortie conduit de cheminée
Salida conducto de humos
Rauchauslass

Ingresso aria
Air inlet
Entrée d'air
Entrada aire
Lufteinlass

Serbatoio pellet
Pellet tank
Reservoir
Depósito
Tank Fassungsvermögen

Absorbimento elettrico
Electrical consumption
Absorption électrique
Consumo de electricidad
Elektrischer Verbrauch

RELAX 9	KW 8,0-24	% 91,9	Kg 157	Kg/H 0,5-1,9	°C 142	Pa 10	mm 80	mm 60	Kg 18,5	W 350-100
RELAX 7	KW 6,5-24	% 93,0	Kg 155	Kg/H 0,5-1,5	°C 121	Pa 10	mm 80	mm 60	Kg 18,5	W 350-100

